




Legacy Panel

The Legacy Panel offers an appealing combination of style and affordability. The 12" on center rib gives the look and feel of standing seam roofing but at a more affordable price. Legacy Panel is great for residential and light commercial projects, combining the protection of steel with an attractive look.

29
Gauge
26
Gauge

3/4"
RIB HEIGHT

RECOMMENDED
3:12
PITCH
AND ABOVE
PER IBC*



Manufactured with a Siphon Groove to minimize leaks and direct water down the panel.

Wide fastening surface for easy installation and defined panel ribs for clear screw placement.

Unique lap groove that hides the overlap providing a smooth, clean appearance.

29 GAUGE THICKNESS								
SPAN TYPE	LOAD TYPE	SUPPORT SPACING						
		2 Ft.	2.5 Ft.	3 Ft.	3.5 Ft.	4 Ft.	4.5 Ft.	5 Ft.
1-SPAN	NEGATIVE WIND LOAD	76.55	48.99	34.02	25.00	19.14	15.12	12.25
	LIVE LOAD/DEFLECTION - L/60	99.36	63.59	44.16	32.45	24.84	19.63	15.90
	LIVE LOAD/DEFLECTION - L/180	86.19	44.13	25.54	16.08	10.77	7.57	5.52
	LIVE LOAD/DEFLECTION - L/240	64.64	33.10	19.15	12.06	8.08	5.67	4.14
2-SPAN	NEGATIVE WIND LOAD	93.95	61.31	43.04	31.84	24.48	19.40	15.75
	LIVE LOAD/DEFLECTION - L/60	73.99	47.92	33.50	24.71	18.97	15.02	12.18
	LIVE LOAD/DEFLECTION - L/180	73.99	47.92	33.50	24.71	18.97	15.02	12.18
	LIVE LOAD/DEFLECTION - L/240	73.99	47.92	33.50	24.71	18.97	14.32	10.44
3-SPAN	NEGATIVE WIND LOAD	114.79	75.48	53.16	39.06	29.90	23.63	19.14
	LIVE LOAD/DEFLECTION - L/60	86.59	59.35	41.60	30.74	23.62	18.71	15.19
	LIVE LOAD/DEFLECTION - L/180	86.59	59.35	41.60	30.74	21.00	14.75	10.75
	LIVE LOAD/DEFLECTION - L/240	86.59	59.35	41.60	23.51	15.75	11.06	8.07
4-SPAN	NEGATIVE WIND LOAD	107.99	70.82	49.86	36.95	28.44	22.56	18.33
	LIVE LOAD/DEFLECTION - L/60	83.35	55.57	38.92	28.74	22.08	17.49	14.19
	LIVE LOAD/DEFLECTION - L/180	83.35	55.57	38.92	28.74	22.08	15.73	11.47
	LIVE LOAD/DEFLECTION - L/240	83.35	55.57	38.92	25.07	16.80	11.80	8.60

26 GAUGE THICKNESS								
SPAN TYPE	LOAD TYPE	SUPPORT SPACING						
		2 Ft.	2.5 Ft.	3 Ft.	3.5 Ft.	4 Ft.	4.5 Ft.	5 Ft.
1-SPAN	NEGATIVE WIND LOAD	110.60	70.79	34.02	36.12	27.65	21.85	17.70
	LIVE LOAD/DEFLECTION - L/60	142.30	91.07	44.16	46.46	35.57	28.11	22.77
	LIVE LOAD/DEFLECTION - L/180	120.15	61.52	25.54	22.42	15.02	10.55	7.69
	LIVE LOAD/DEFLECTION - L/240	90.11	46.14	19.15	16.81	11.26	7.91	5.77
2-SPAN	NEGATIVE WIND LOAD	133.88	87.51	43.04	45.51	35.01	27.76	22.54
	LIVE LOAD/DEFLECTION - L/60	106.51	69.08	33.50	35.66	27.38	21.68	17.59
	LIVE LOAD/DEFLECTION - L/180	106.51	69.08	33.50	35.66	27.38	21.68	17.59
	LIVE LOAD/DEFLECTION - L/240	106.51	69.08	33.50	35.66	27.38	19.84	14.46
3-SPAN	NEGATIVE WIND LOAD	163.28	107.59	53.16	56.39	43.20	34.14	27.65
	LIVE LOAD/DEFLECTION - L/60	131.06	85.45	41.60	44.34	34.09	27.01	21.92
	LIVE LOAD/DEFLECTION - L/180	131.06	85.45	41.60	43.78	29.33	20.60	15.02
	LIVE LOAD/DEFLECTION - L/240	131.06	85.45	41.60	32.83	22.00	15.45	11.26
4-SPAN	NEGATIVE WIND LOAD	153.71	101.00	49.86	52.79	40.67	32.27	26.22
	LIVE LOAD/DEFLECTION - L/60	123.00	80.05	38.92	41.46	31.86	25.24	20.48
	LIVE LOAD/DEFLECTION - L/180	123.00	80.05	38.92	41.46	31.20	21.91	15.98
	LIVE LOAD/DEFLECTION - L/240	123.00	80.05	38.92	34.93	23.40	16.44	11.98



SPECIFICATION

Available Gauges: **29 & 26**

Steel Thickness: **0.0142" for 29g**
0.0185" for 26g

Paint System: **SHERWIN-WILLIAMS**
Coil Coatings **SMP** WeatherXL™

Warranty:
40 Year Lifetime Limited Paint Adhesion
30 Year Chalk and Fade

Rust Protection Substrate:
Galvalume AZ50

Testing:

- UL 580 Uplift (Class 90)
- UL 2218 Class 4 Impact Resistance
- UL 790 Class A Fire Rating



Delta Metals is neither partially nor solely responsible for improper installation or defects as a result of improper installation.

Application Details


Fastener Guide:

We recommend using our
#10 Woodbinder screws with dimensional lumber,
plywood sheeting and OSB. (7/16" minimum thickness
for decking materials)
#12 MTM Self Drilling Screws are designed to be used
with structural steel up to 3/16" in thickness

Fastener Application:

Screws are to be applied next to every rib and then up the panel, no more than 3'. For slopes of 2/12 or less it is recommended to use mastic tape between the panel side laps with stitch screws installed every 1' up the panel. At the eave or end laps a double screw pattern should be used with screws applied to both sides of the rib.

Screw Patterns:



Please Note: It is the responsibility of the builder to ensure that purlins are adequately spaced to meet specific engineering requirements.

1796 Hwy 50 Delta, CO 81416 (970) 874-7070



SHERWIN-WILLIAMS
Coil Coatings